ADAS FIND

Date of Report: 2025-09-28
Retail Price: $12 USD plus taxes
Location: ADAS Find LLC.
1664 Grand River Ave.
East Lansing, Michigan 48823

ADAS & Safety Requirement Report:

Vehicle: 2023 TOYOTA Prius
Insurance: SELF PAY

VIN: 1XXXXXXXXXXXXXXX
RO: 12345

Equipped ADAS Features:

- BackUp Camera
- Millimeter Wave Radar
- Front Side Radar
- Forward Recognition Camera
- Blind Spot Monitor Sensor

- Front Ultrasonic Sensors
- Rear Ultrasonic Sensors
- Surround View Cameras
- Blind Spot Intervention

Programming / Initialization Actions: 2

• Steering Angle Sensor

Line Caught: 90* R&I Battery (D&R) 0 0.00m 0.2M 0.0
Initialization Requirement: Battery disconnect
OEM Reference: ADAS Initialization Requirement Link (Requires ALLDATA subscription)
Procedure: ADAS Initialization Procedure Link (Requires ALLDATA subscription)
Calibration Type: RESET

• Yaw Rate Sensor

Line Caught: 95# Subl Wheel Alignment 1 89.00X 0.0 0.0
Initialization Requirement: wheel alignment has been adjusted
OEM Reference: ADAS Initialization Requirement Link (Requires ALLDATA subscription)
Procedure: ADAS Initialization Procedure Link (Requires ALLDATA subscription)
Calibration Type: RESET

ADAS Calibrations: 3

• Blind Spot Monitor Sensor

Line Caught: 3 * <> Rpr Bumper cover w/panoramic view 0 0.00 1.0 2.8
Requirement: After any body repair
OEM Reference: ADAS Calibration Requirement Link (Requires TIS Access)
Alternative Reference: ADAS Calibration Requirement Link (Requires ALLDATA subscription)
Procedure: ADAS Calibration Procedure Link (Requires ALLDATA subscription)
Calibration Type: STATIC
Calibrate With Bumper: ON

- **Rear Ultrasonic Sensors**

    Line Caught: 11 S01 Repl Add for park sensor 1 0.00m 0.7 0.0

    Requirement: Removal and installation or replacement

    OEM Reference: ADAS Calibration Requirement Link (Requires TIS Access)

    Alternative Reference: ADAS Calibration Requirement Link (Requires ALLDATA subscription)

    Procedure: ADAS Calibration Procedure Link (Requires ALLDATA subscription)

    Calibration Type: STATIC

- **Surround View Cameras**

    Line Caught: 69 R&I RT R&I mirror 0 0.00 0.3 0.0

    Requirement: Replacement or removal and installation

    OEM Reference: ADAS Calibration Requirement Link (Requires TIS Access)

    Alternative Reference: ADAS Calibration Requirement Link (Requires ALLDATA subscription)

    Procedure: ADAS Calibration Procedure Link (Requires ALLDATA subscription)

    Calibration Type: STATIC

Safety Actions: 3

- **OEM Pre-Scan and Post-Scan**

    Requirement: After ANY collision occurs

    OEM Reference: Pre- & Post-Scan Position Statement

- **Occupancy Detection System Rezeroing**

    Requirement: After ANY collision occurs

    OEM Reference: ADAS Safety Action Link

- **Seat Belt System Check**

    Requirement: After ANY collision occurs

    OEM Reference: ADAS Safety Action Link

ADAS FIND